BA201

BA201 ist ein mikroprozessorgesteuertes, CAN-BUS-fähiges Lade-Diagnose- und Testgerät für 12V Bleibatterien (Gel, EXIDE, AGM, Hawker, Microflies und Säure), sowie nach Umschaltung auch für moderne Lithium-Batterien. Es arbeitet mit kennlinien-gesteuerter Ladetechnik und sorgt für optimale Ladung und Akkupflege. Im Lieferumfang befindet sich das komplette Anschlusszubehör.

- Mikroprozessor - Mehrstufen I/U- Ladekennlinie
- Ladestrom max. 2A (automatische Anpassung) mit Erhaltungsladen
- Automatische Lade- Batterietest- und Diagnosefunktion, Defekterkennung
- Umschaltbar zw. Blei, Gel, AGM, EXIDE, Hawker **- LITHIUM** Akkus
- **CAN-BUS** tauglich
- Automatischer Batteriepflegemodus (Entsulfatierung)
- Verpol- und kurzschlusssicher
- Funkenfrei – kein Ausbau der Batterie erforderlich
- 7 LED: (Power / Pb / Li / LADEN / VERPOLT / FERTIG / DEFEKT)
- Anschlusszubehör: Universal-Stecker, vollisolierte Zangen, Batterie-Kabel

---

BA201 is a modern, intelligent battery charging and diagnostic tester with 2A/ 12V also for CAN-BUS. It is switchable for lead-acid batteries (gel, Exide, AGM, Hawker) or Ltihium. It works with characteristic controlled charging technology, allows for optimal charging and battery maintenance.

- *Microprozessor charger, Non-sparking*
- *For **CAN-BUS** technology*
- *Protection of electronic short circuit, wrong polarity + overcharging*
- *Switchable for Lead, Gel, AGM, EXIDE, Hawker or **Lithium** batteries*
- *Charging current max. 2 A (automatic charge control)*
- *7 LED status displays*
- *With universal connector, battery cable and fully insulated clamps*

Technische Daten / *Technical datas:*

■ **Betriebsspannung / Operating voltage:**	**220-240 V / AC 50 Hz**
■ **Ladestrom / Charging current:**	**max. 2 A (autom.)**
■ **Spannung / Voltage:**	**12V**
■ **Ladeschlussspannung / Charging voltages:**	**7,15 /14,3 V (U1 Phase)**
■ **Empfohlene Batteriekapazität / Recommended for:**	**1,2 - 100 Ah**
■ **Umgebungstemperatur / Surrounding temperature:**	**5 – 50° C**
■ **Maße, Gewicht / Dimensions weight:**	**165 x 82 x 47 mm / 608 g**